

EC TYPE-EXAMINATION CERTIFICATE MODULE B

0407-MED-152 (IG-102-2014)

This is to certify that the product
SINGLE FIRE DOOR CAPRI

Reg. (EU) 2018/773 Item
MED/3.16 - Fire Doors

Applicant
PRIMICERI S.p.A.
Via della Azalee, 10 - 70123 BARI (BA) - Italy

it has been submitted to tests identified in the annex to this certificate
in compliance with the module B scheme of directive 2014/90/EU

This certificate will not be valid if the manufacturer makes any changes or modifications to the approved
equipment, which have not been notified to and agreed with Istituto Giordano

Bellaria-Igea Marina - Italy, 30 October 2019

Date of first issue: 7 May 2014

Revision No. 1

Expiration date: 29 October 2024

MED Department Technical Manager
(Dott. Ing. Giuseppe Persano Adorno)

Chief Executive Officer

This certificate is made up of 2 pages and remains valid until expiry unless cancelled or revoked, provided the conditions in the attached schedule are complied with and the equipment remains satisfactory in service.

Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be reappraised prior to it/they being placed on board vessels to which the amended regulations or standards apply.

This certificate and the documents should be stored for ten years after the last product has been manufactured.

The validity of this certificate is subject to compliance with Istituto Giordano "REG-MED" rules, the Istituto Giordano general conditions of contract for certification and the relevant requirements of Marine Equipment Directive.


The original of this document consists of an electronic document digitally signed pursuant to the applicable Italian Legislation.

Page 1 of 2

Specified standard	IMO Res.MSC.307(88)-(2010 FTP Code), as amended. IMO MSC.1/Circ.1319.
Regulation SOLAS 74 as amended	Type approval requirements - SOLAS 74 Reg. II-2/9.
Approval documentation	Test report Istituto Giordano No. 315413 of 30 April 2014. Technical documentation of the product attached to the test reports aforementioned.
Restrictions	"A60" Class Door - Exposed side with panic push bar.
Product description	Single fire door as follows. External dimensions 982 × 2500 mm. Frame of the door made in steel sheet S275JO bent, thickness 4 mm. Sheet of closure made in S275JO, thickness 1,2 mm. Internal insulation "SKAMOL Super Pro 300". TECNOFLAME seals with adhesive mod. TP212040S (MAVRON S.r.l.).
Manufacturer	PRIMICERI S.p.A. - Via della Azalee, 10 - 70123 BARI (BA) - Italy.

Revision legend		
No.	Date	Scope
0	7 May 2014	First issue
1	30 October 2019	Renewal

Notes:

The mark of conformity ("wheelmark") may only be affixed to the above type approved equipment and a manufacturer's declaration of conformity issued when the production-control phase module (D, E, or F) of annex B of the Directive is fully complied with and controlled by a written inspection agreement with a Notified Body.		
 YYYY/XX	YYYY	Notified Body number undertaking surveillance module.
	XX	Last two digits of year mark affixed.